

MAXIBAR 300

300T pipe spreader

Load Chart

LENGTH	WLL (T)		APPROXIMATE SLING LEG LENGTH (Mtrs)		APPROXIMATE HEADROOM (Mtrs)		COMBINATIONS								TARE KG
	60°	90°	60°	90°	60°	90°	End Lugs	0.5Mtr	1.0Mtr	2.0Mtr	4.0Mtr	5.0Mtr	5.5Mtr	6.0Mtr	
2.0	300.0	200.0	2.000	1.414	1.733	1.000	2								1600
2.5	300.0	200.0	2.500	1.768	2.167	1.250	2	1							1700
3.0	300.0	200.0	3.000	2.121	2.600	1.500	2		1						1850
3.5	300.0	200.0	3.500	2.475	3.033	1.750	2	1	1						2000
4.0	300.0	200.0	4.000	2.828	3.466	2.000	2			1					2050
4.5	300.0	200.0	4.500	3.182	3.900	2.250	2	1		1					2200
5.0	300.0	200.0	5.000	3.535	4.333	2.500	2		1	1					2300
5.5	300.0	200.0	5.500	3.889	4.766	2.750	2	1	1	1					2450
6.0	300.0	200.0	6.000	4.242	5.200	3.000	2				1				2420
6.5	300.0	200.0	6.500	4.596	5.633	3.250	2	1			1				2550
7.0	300.0	200.0	7.000	4.949	6.066	3.500	2		1		1				2600
7.5	300.0	200.0	7.500	5.303	6.500	3.750	2						1		2700
8.0	300.0	200.0	8.000	5.656	6.933	4.000	2	1						1	2850
8.5	300.0	200.0	8.500	6.010	7.366	4.250	2		1					1	2950
9.0	300.0	200.0	9.000	6.363	7.799	4.500	2	1	1					1	3100
9.5	300.0	200.0	9.500	6.717	8.233	4.750	2			1				1	3150
10.0	300.0	200.0	10.000	7.070	8.666	5.000	2	1		1				1	3300
10.5	300.0	200.0	10.500	7.424	9.099	5.250	2		1	1				1	3400
11.0	300.0	200.0	11.000	7.777	9.533	5.500	2				1	1			3400
11.5	300.0	200.0	11.500	8.131	9.966	5.750	2				1		1		3500
12.0	300.0	200.0	12.000	8.484	10.399	6.000	2				1			1	3600
12.5	300.0	200.0	12.500	8.838	10.833	6.250	2					1	1		3700
13.0	300.0	200.0	13.000	9.191	11.266	6.500	2					1		1	3800
13.5	250.0	200.0	13.500	9.545	11.699	6.750	2						1	1	3900
14.0	250.0	200.0	14.000	9.898	12.132	7.000	2	1						1	4050
14.5	250.0	200.0	14.500	10.252	12.566	7.250	2		1					1	4150
15.0	250.0	200.0	15.000	10.605	12.999	7.500	2			1			1	1	4250
15.5	250.0	200.0	15.500	10.959	13.432	7.750	2			1	1		1	1	4300
16.0	250.0	200.0	16.000	11.312	13.866	8.000	2		1	1		1		1	4500
16.5	250.0	200.0	16.500	11.666	14.299	8.250	2		1	1			1	1	4600
17.0	250.0	200.0	17.000	12.019	14.732	8.500	2				1	1		1	4600
17.5	250.0	200.0	17.500	12.373	15.166	8.750	2				1		1	1	4700
18.0	250.0	200.0	18.000	12.726	15.599	9.000	2	1			1			1	4850
18.5	250.0	200.0	18.500	13.080	16.032	9.250	2		1		1			1	4950
19.0	250.0	200.0	19.000	13.433	16.465	9.500	2	1				1	1	1	5050
19.5	250.0	200.0	19.500	13.787	16.899	9.750	2		1			1	1	1	5150
20.0	250.0	200.0	20.000	14.140	17.332	10.000	2	1	1			1	1	1	5300
20.5	250.0	150.0	20.500	14.494	17.765	10.250	2			1		1	1	1	5350
21.0	250.0	150.0	21.000	14.847	18.199	10.500	2	1		1		1	1	1	5500
21.5	250.0	150.0	21.500	15.201	18.632	10.750	2		1	1		1	1	1	5600
22.0	250.0	150.0	22.000	15.554	19.065	11.000	2	1	1	1		1	1	1	5750
22.5	200.0	110.0	22.500	15.908	19.499	11.250	2				1	1	1	1	5700
23.0	200.0	110.0	23.000	16.261	19.932	11.500	2	1			1	1	1	1	5900
23.5	200.0	110.0	23.500	16.615	20.365	11.750	2		1		1	1	1	1	5950
24.0	200.0	110.0	24.000	16.968	20.798	12.000	2	1	1		1	1	1	1	6150
24.5	150.0	90.0	24.500	17.322	21.232	12.250	2			1	1	1	1	1	6150
25.0	150.0	90.0	25.000	17.675	21.665	12.500	2	1		1	1	1	1	1	6300
25.5	150.0	90.0	25.500	18.029	22.098	12.750	2		1	1	1	1	1	1	6400
26.0	150.0	90.0	26.000	18.382	22.532	13.000	2	1	1	1	1	1	1	1	6600

MAXIBAR 300

300T pipe spreader

Top Shackle:
200T Van Beest Sling Saver Shackle

Bottom Shackle:
150T Van Beest Sling Saver Shackle

